

616T11X - ThermoLyn supra

Material number 616T11X

Page: 1 of 7

1. Product and company identification**Product identifier**

Trade name: 616T11X - ThermoLyn supra

Relevant identified uses of the substance or mixture and uses advised against

General use: Article for orthopedic procedures.

Processing at Processing temperature and Forming temperature
(refer to section 9: Physical and chemical properties)**Details of the supplier of the safety data sheet**Company name: Otto Bock Health Care
Street/POB-No.: 3820 W. Great Lakes Drive
Postal Code, city: Salt Lake City, UT 84120
USAWWW: www.ottobockus.com

Telephone: +1 (801) 956-2400

Telefax: +1 (801) 956-2401

Dept. responsible for information:

Quality Department,
Telephone: +1 (801) 954-2304 (7 AM – 3 PM, Mountain Time),
Email: USRegulatory@ottobock.com

Additional information: This safety data sheet pertains to the following products:

Article No. 616T111 - ThermoLyn supra soft plus Silikon

Article No. 616T112 - ThermoLyn supra flexible

Article No. 616T113 - ThermoLyn supra flexible

Corporate headquarters:

Ottobock SE & Co. KGaA

Max-Näder-Straße 15

Duderstadt

Germany

Emergency phone number**CHEMTREC, Telephone: +1 (800) 424-9300****2. Hazards identification****Emergency overview**Appearance: Form: solid, plate
Color: varying, depends on colouring

Odor: acidic

Classification: This substance is classified as not hazardous.

Regulatory status

This material is not considered hazardous by the U.S. OSHA Hazard Communication Standard (29 CFR 1910.1200) and SIMDUT in Canada.

Hazards not otherwise classified

Processing by heating can produce vapours. Processing, e.g. by cutting, sawing or grinding, can produce particles and dust. For risks which have to be observed thereby, see section 7: Handling, section 8: Exposure controls / personal protection and section 11: Toxicology.

In case of heating: risk of burns.

Danger of cutaneous absorption.

dust/vapors: mild irritant

see section 11: Toxicological information

3. Composition / Information on ingredients

Chemical characterization: copolymer based on Ethylene and Vinyl acetate (EVA) and Silicone (616T111), pigments (inorganic).

4. First aid measures

General information: For mechanical processing: dust formation.
Processing by heating can produce vapours.

In case of inhalation: Dusts/vapors:
Provide fresh air. Seek medical treatment in case of troubles.

Following skin contact: Remove residues with water. Seek medical treatment in case of troubles.
If burned by hot product, quench immediately with cold tap water.
Do not peel solidified product off the skin. Immediately get medical attention.

After eye contact: Dusts/vapors:
Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart.
In case of troubles or persistent symptoms, consult an ophthalmologist.

Most important symptoms/effects, acute and delayed

In case of heating: risk of burns.

Danger of cutaneous absorption.

dust/vapors: mild irritant

Information to physician

Treat symptomatically.

5. Fire fighting measures

Flash point/flash point range:
> 500 °F

Auto-ignition temperature: not self-igniting

Suitable extinguishing media:
Water spray jet, foam, dry chemical powder, carbon dioxide.

Extinguishing media which must not be used for safety reasons:
Full water jet,

Specific hazards arising from the chemical

Harmful and/or toxic vapors may be produced in the event of thermal decomposition. In case of fire may be liberated: acetic acid-vapors, nitrogen oxides (NOx), Vinyl acetate, alcohol, aldehydes, Silicone, carbon monoxide and carbon dioxide.

Protective equipment and precautions for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing.

6. Accidental release measures

- Personal precautions: Suitable protective clothing. Keep unprotected people away.
In case of development of vapors or dust:
Provide fresh air. Do not inhale vapors or dust particles. Wear protective equipment.
- Environmental precautions: Do not allow to penetrate into soil, waterbodies or drains.
- Methods for clean-up: Take up mechanically, placing in appropriate containers for disposal.

7. Handling and storage

Handling

- Advices on safe handling: Provide adequate ventilation, and local exhaust as needed.
Processing: Make sure that the processing machines are well equipped with suction and ventilation systems.
If necessary: With the formation of dust, use a dust mask.
In case of development of vapors or dust:
Provide fresh air. Do not inhale vapors or dust particles. Wear protective equipment.
- Precautions against fire and explosion: Avoid open flames.
Take precautionary measures against static discharges.

Storage

- Requirements for storerooms and containers: Keep only in the original container.
Keep container tightly closed and dry. Protect from moisture contamination.
Protect against direct sunlight.
storage temperature: 50 - 86 °F
- Hints on joint storage: Avoid contact with acids and bases .

8. Exposure controls / personal protection

Exposure guidelines

Occupational exposure limit values:

Type	Limit value
USA: ACGIH: TWA	10 mg/m ³
USA: ACGIH: TWA	3 mg/m ³
USA: OSHA: TWA	15 mg/m ³
USA: OSHA: TWA	5 mg/m ³

Engineering controls

Provide for constant fresh air supply during and after processing.
See also information in chapter 7, section storage.

Personal protection equipment (PPE)

- Eye/face protection: Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010.
- Skin protection: Suitable protective clothing.
protective gloves according to OSHA Standard - 29 CFR: 1910.138
If necessary:
Protective gloves against thermic risks.
For machine processing:
Protective gloves against mechanical risks.
OSHA Standard - 29 CFR: 1910.138
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.
- Respiratory protection: When vapors form: Use combination filter type A, B, E according to OSHA Standard - 29 CFR: 1910.134 or ANSI Z88.2.
For mechanical processing: Half mask with particle filter P according to OSHA Standard - 29 CFR: 1910.134 or ANSI Z88.2.
- General hygiene considerations:
When using do not eat, drink or smoke. Avoid generation of dust.
Wash hands before breaks and after work.
The following shall be existing in the immediate working surrounding: emergency shower installed.

9. Physical and chemical properties

Information on basic physical and chemical properties

- Appearance: Form: solid, plate
Color: varying, depends on colouring
- Odor: acidic
- Odor threshold: No data available
- pH value: No data available
- Melting point/freezing point: No data available
- Initial boiling point and boiling range: No data available
- Flash point/flash point range: > 500 °F
- Evaporation rate: No data available
- Flammability: No data available
- Explosion limits: No data available
- Vapor pressure: No data available
- Vapor density: No data available
- Density: at 68 °F: 0.95 g/cm³
- Solubility: chloroform: soluble
- Water solubility: insoluble
- Partition coefficient: n-octanol/water: No data available
- Auto-ignition temperature: not self-igniting
- Thermal decomposition: > 200 °C
- Explosive properties: Product is not explosive.

Additional information: softening range: 176 - 194 °F
 Processing temperature, Recommendation: 302 °F

10. Stability and reactivity

Reactivity: refer to section 10.3

Chemical stability: Stable under recommended storage conditions.

Possibility of hazardous reactions
 No dangerous reactions are known.

Conditions to avoid: Protect from moisture contamination. Keep away from heat.
 Protect against direct sunlight.
 Processing: Avoid temperatures exceeding 302 °F.

Incompatible materials: Avoid contact with acids and bases .

Hazardous decomposition products:
 If heated to decomposition product may emit: Monomer(s).
 In case of fire may be liberated: acetic acid-vapors, nitrogen oxides (NOx), Vinyl acetate, alcohol, aldehydes, Silicone, carbon monoxide and carbon dioxide.

Thermal decomposition: > 200 °C

11. Toxicological information

Toxicological tests

Toxicological effects: Acute toxicity (oral): Based on available data, the classification criteria are not met. LD50 Rat, oral: 2920 mg/kg
 Acute toxicity (dermal): Based on available data, the classification criteria are not met. LD50 Rat, dermal: 2335 mg/kg
 Acute toxicity (inhalative): Based on available data, the classification criteria are not met. LD50 Rat, inhalative: 4000 ppm
 Skin corrosion/irritation: Lack of data.
 Serious eye damage/irritation: Lack of data.
 Sensitisation to the respiratory tract: Lack of data.
 Skin sensitisation: Lack of data.
 Germ cell mutagenicity/Genotoxicity: Lack of data.
 Carcinogenicity: Lack of data.
 Reproductive toxicity: Lack of data.
 Effects on or via lactation: Lack of data.
 Specific target organ toxicity (single exposure): Lack of data.
 Specific target organ toxicity (repeated exposure): Lack of data.
 Aspiration hazard: Lack of data.

Other information: Vinyl acetate:
 skin: mild irritant. Causes serious eye irritation.

616T11X - ThermoLyn supra

Material number 616T11X

Page: 6 of 7

Symptoms

In case of heating: risk of burns.

In case of inhalation: dust/vapors: mild irritant

After contact with skin: Danger of cutaneous absorption.

After eye contact: dust/vapors: mild irritant

12. Ecological information**Ecotoxicity**

Further details: No data available

Mobility in soil

No data available

Persistence and degradability

Further details: Product is not biodegradable.

Additional ecological information

General information: Do not allow to penetrate into soil, waterbodies or drains.

13. Disposal considerations**Product**

Recommendation: Incinerate according to applicable local, state and federal regulations.

Contaminated packaging

Recommendation: Dispose of waste according to applicable legislation.

Non-contaminated packages may be recycled.

14. Transport information**USA: Department of Transportation (DOT)**

Proper shipping name: Not restricted

Sea transport (IMDG)

Proper shipping name: Not restricted

Marine pollutant: no

Air transport (IATA)

Proper shipping name: Not restricted

Further information

No dangerous good in sense of these transport regulations.

15. Regulatory information

National regulations - Great Britain

Hazchem-Code: -

16. Other information

Hazard rating systems:



NFPA Hazard Rating:

Health: 1 (Slight)

Fire: 1 (Slight)

Reactivity: 0 (Minimal)

HMIS Version III Rating:

Health: 1 (Slight)

Flammability: 1 (Slight)

Physical Hazard: 0 (Minimal)

Personal Protection: X = Consult your supervisor

HEALTH	1
FLAMMABILITY	1
PHYSICAL HAZARD	0
	X

Literature: At processing: See information supplied by the manufacturer.

Reason of change: Changes in section 1.3: Corporate headquarters

Date of first version: 5/14/2013

Department issuing data sheet

Contact person: see section 1: Dept. responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.