## ottobock.

# **Genium X4 – Prosthetic knee joint.** Order form.

Contact person		Cus	stomer no	).	Date	
Customer				Shipping address (if	different from custo	omer address)
Company				Company		
Address				Address		
City/State				City/State		
Postal code				Postal code		
Email				Email		
Gender	Female	Male		Mobil	ity Grade	
				Mok	oility Grade 2	
Weight	lbs			Mok	oility Grade 3	
Foot size	cm			Mok	oility Grade 4	
Side of amputation	left right	bilateral		Ampu	ıtation Level	
Prosthetic attachment				_	e Disarticulation	٦
to residual limb	Conventiona	Lsocket	Transfemoral			
to residuat iiiib		chored implant		Hip	Disarticulation,	/ Hemipelvectomy
Fitting		والممالية مناهما		ov. Ottobook		
Initial fitting (of microp		sthetic knee joint				
	Manufacturer			Model		
	previous pro	sthetic knee join				
	no previous	prosthetic knee j	oint			
Follow-up fitting (of m		-		-		
	→ previous m	icroprocessor co	ntrolled	d knee joint		
	Model			Serial number		

### ottobock.

AXON Tube adapter (torsion unit=

Quickchange connecting element

with thread

weatherproof, not corrosion resistant)

## **Genium X4 – Prosthetic knee joint.**Order form.

**AXON Tube adapter** 

(waterproof and corrosion resistant)

#### **Knee joint**

Includes the following additional components: 757L48=1 AC Adapter (EU and US compatible), 757L47=1 USB Adapter for charging, 4H110=7.5 Flexion Stop 7.5°, 4H110=15 Flexion Stop 15° (pre-assembled), 4H110=22.5 Flexion Stop 22.5°.

#### Warranty (please choose one)

2R68=280

SP-3B5-4=3 3-year warranty package	SP-3B5-4=6 6-year warranty package	
------------------------------------	------------------------------------	--

3-year standard warranty package included at the time of product purchase. 6-year extended warranty can be purchased at the time of product purchase. A 3 to 6 year warranty extension can be purchased within 36 months of initial purchase.

2R69=280

4R11=ST-1-1

#### **Electronic Tube Adapter**

Connectio	n componer	ts				
	4R47=5.0 Refit adapter for lamination anchor			4R11=P-1-3	Quickchange set with pyramid	
	4R48=5.0	Refit socket adapter		4R11=R-1-3	Quickchange set with pyramid receiver	
	4R57=WR	Rotation adapter (waterproof and corrosion resistant)		4R11=ST-1-3	Quickchange set with thread	
	4R57=WR-ST	Rotation adapter screw top (waterproof and corrosion resistant)		4R11=R-3-2	Quickchange base element with pyramid receiver	
				4R11=P-1-1	Quickchange connecting element with pyramid	
				4R11=R-1-1	Quickchange connecting element with pyramid receiver	

#### **Foot components**

1A1-2		Empower		1C63	Triton Low Profile <sup>2</sup>
1B1-2		Meridium		1C64	Triton Heavy Duty <sup>2</sup>
1C30-	1	Trias		1C68	Triton side flex <sup>2</sup>
1C40		C-Walk		1C70	Evanto
1C60		Triton		1D35	Dynamic Motion
1C61		Triton Vertical Shock		1E56	Axtion
1C62		Triton Harmony		1E95	Challenger
Color of footshell beige light brown					

Shape of footshell slim	normal				
1C50	Taleo <sup>2</sup>		F21	Maverick Xtreme	AT <sup>2</sup>
1C51	Taleo Vertical Shock		F22	Maverick Comfort AT <sup>2</sup>	
1C52	Taleo Harmony		F23	Maverick Vertical	. Shock
1C53	Taleo Low Profile <sup>2</sup>	Activity level	low	moderate	high
1C56	Taleo Adjust	Color of foot	<b>shell</b> light	medium	dark
1C58	Taleo Side Flex <sup>2</sup>		LP2-W2	Freestyle Swim²	

Activity level normal high
Color of footshell beige light brown¹
Shape of footshell slim¹ normal

In combination with a prosthetic knee joint, some foot sizes and stiffnesses may be excluded. Please follow the information in the foot order sheet and the instructions for use. In case of any questions, please contact Ottobock customer service.

Please submit completed order form to: CACustomerService@ottobock.com **shop.ottobock.ca** | P 800 665 3327 | F 800 463 3659

<sup>&</sup>lt;sup>1</sup>Not available for all feet and/or sizes. Please visit our homepage for more information.

 $<sup>^{\</sup>rm 2}\,\mbox{Recommended}$  combination, because of water & corrosion resistant components.

## ottobock.

## Genium X4 – Prosthetic knee joint. Order form.

#### **Cover Solutions**

4P100=7	Genium X4 Protective cover, short	3D13=1	Thigh kit/Magnetic closure		osure
4P110=7	Genium X4 Protective cover, long	3F2=0	Functional cosmesis Genium X4		Genium X4
4P112=1	Functional knee part	99B122	Functional stocking		
			Size Color	S beige-4	L light brown-15

#### Accessories Included in scope of delivery.

	757L48=1	AC Adapter	4H110=7.5	Flexion Stop 7.5°
	757L47=1	USB Adapter for charging	4H110=15	Flexion Stop 15°
Ī			4H110=22.5	Flexion Stop 22.5°

The General Terms and Conditions of Ottobock SE & Co. KGaA apply. The expected lifetime given compliance with the prescribed maintenance intervals is 6 years. For additional information please contact / visit:

Date Place Signature